

# 9330 Monochrome Laser Printer

## Transform Your Business



- Print Speed Up to 30 ppm
- Choice of models Simplex or Duplex
- Small and compact design
- 1200 x 1200 dpi print quality
- 8.5 Seconds first time to print
- Ideal for workgroups or small networks

### Small and Efficient

Ideally suitable for workgroups or small networks, the feature rich 9330 mono laser printer will transform your documents increasing overall efficiency in your office. True 1200 dpi print quality coupled with a fast 30 page per minute print speed, it delivers professional quality output all within your budget.

### Choice of Models

The **9330N** offers two input paths, a 250 sheet cassette together with a 50 sheet multi-purpose feeder ideal for those non standard paper sizes . PCL and PostScript 3 is standard together with 64 Mb of onboard memory expandable to 320 Mb, will ensure the 9330N will speed through the most complex applications.

For duplex printing, the **9330ND** comes complete with its own built-in duplexer for hassle-free double sided printing on a wide variety of paper types and sizes. Both models can benefit from an additional optional 250 sheet cassette which can be easily added.

### Versatile

USB 2.0 connectivity is standard on all models together with Ethernet 10/100BaseT and parallel, making the 9330 the most versatile printers available today. With a small footprint, it is ideally suited where space is at a premium.

---

Available Configuration:

**9330N** - Simplex model  
**9330ND** - Duplex model

<b>Print Speed</b>	Up to 30 ppm
<b>Print Method</b>	Laser
<b>Processor</b>	SPGPv3 processor at 400 MHz
<b>Resolution</b>	1200 x 1200 dpi
<b>Time To 1st Page</b>	From ready mode: < 8.5 seconds; From power save mode: 39 sec.
<b>Memory</b>	64MB Standard, 320MB Maximum
<b>Standard Connectivity</b>	Parallel (Bi-directional IEEE 1284 compliant ECP/Nibble/Byte Mode), USB (v 2.0), Internal Ethernet (10BaseT & 100BaseTx); Automatic Interface Switching
<b>Standard Emulation</b>	PCL6 / PCL 5e / IBM Proprinter / Epson / Postscript Level 3 PDL, Automatic Emulation Sensing
<b>Print Monitor</b>	SyncThru, SET IP
<b>Fonts</b>	1 Bit Map and 45 scaleable (35 Intellifont, 10 TrueType), 136 PS3 fonts
<b>Consumables</b>	High Yield Cartridge: 8,000 pages; Standard Yield Cartridge: 4,000 pages (Based on 5% coverage)
<b>STD Paper Handling</b>	Manual feed, 50 sheet multi-purpose feeder( MPF ) plus 250 sheet universal cassette
<b>Opt'l Paper Handling</b>	2nd universal cassette accepts 250 sheets
<b>Duplexing</b>	Standard on 9330DN
<b>Paper Drive</b>	Envelope sizes: Monarch, No 9, No 10, C5, DL
<b>Paper Type</b>	MPF - paper, transparencies, labels, heavy paper stock, envelopes; Standard cassette - paper; Optional cassette - paper
<b>Paper Weight</b>	Cassette - 60-90gsm MPF - 60-163 gsm
<b>Paper Size</b>	MPF - A4, A5, A6, Letter, Legal, Folio, Executive, ISO B5, JIS B5, 3" x 5"; Standard Cassette - A4, A5, Letter, Legal, Folio, Executive ISO B5, JIS, 3" x 5"; Optional Cassette - A4, A5, Letter, Legal, Folio, Executive ISO B5, JIS, 3" x 5"
<b>Paper Output</b>	150 sheet face down, 1 sheet face up
<b>Printable Area</b>	Paper - 4mm from each side, 10 mm from top and bottom
<b>Physical Weight</b>	10.6kg (23.3 lbs.) including consumable
<b>PhysicalSize</b>	400 x 433.4 x 285 mm (15.75" x17.1" x 11.2 ")
<b>Power Voltage</b>	120V 50/60Hz or 230V 50/60Hz
<b>Power Consumption</b>	< 11 watts in sleep mode, < 400 watts printing (average); TEC: 3.09 kWh/week
<b>Compliance</b>	< 0.02 parts per million (UL478), RoHS, Microsoft, ISO-compliant, Meditech Approved, Energy Star® Qualified (Duplex model)
<b>Workload</b>	Up to 35,000 pages per month
<b>Reliability MTBF</b>	30,000 pages (Power on 8 hr/day in recommended duty cycle)
<b>Reliability MTTR</b>	30 minutes
<b>Drivers</b>	Windows 9.x/NT 4.0/2000/ME/XP/Vista, MAC OSX, Posters, N-Up, Booklets, Duplex, Forms, Overlays, Watermarks; DOS Print available
<b>Temperature</b>	10°C - 32°C (50°F - 89.6°F)
<b>Humidity</b>	10% - 80% relative humidity, non-condensing
<b>Altitude</b>	2,500 metres (82,000 feet) maximum
<b>Acoustic</b>	Printing - 54 dBA, Standby - 39 dBA, Sleepmode - Background Level
<b>Warranty</b>	One year, return to depot
<b>Option 1</b>	2nd cassette (250 sheet), 16/32/64/128Mb Memory
<b>Note</b>	Paper is a highly variable medium, and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operating conditions.



© 2009 Printronix, Inc. All rights reserved. Genicom, Tally, TallyGenicom, TG TallyGenicom, the TG Logo, Intellifilter, Intelliprint and Intellipress are trademarks or registered trademarks of Printronix, Inc. Microsoft, Windows, and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. All other trademarks, product names, company names or logos herein are the property of their respective owners. Product appearance and/or specifications are subject to change without notice.

Printed Date: 16/05/2009

## PRINTRONIX®

GLOBAL PRINTING...ENABLED.

14600 Myford Road  
Irvine, CA 92606  
800-665-6210  
www.tallygenicom.com